



\*KEEP © CIEAR \* \*

-Brid Lifts www.hybridiires.com

M1/

1a

## HB-1230CE SELF-PROPELLED AERIAL WORK PLATFORM

# FEATURES & SPECIFICATIONS **HB-1230CE**

#### ZERO TURN RADIUS

Maneuver quickly and easily through congested work sites, through doorways and around tight corners.

#### PROPORTIONAL LIFT AND DRIVE

User-friendly joystick control offers smooth lift and speed control.

#### LARGE WORK PLATFORM

Includes 76.2 cm slide out deck extension for extra supplies and manpower, extension is supported midrail to eliminate jams.

#### MAINTENANCE FREE

Maintenance free AGM Batteries and easy access panels improve life cycle and cost of ownership.

#### LOW FLOOR LOADING

Lightweight design makes the lift easy to manuver and allows for use on delicate or sensitive surfaces.

#### USER-FRIENDLY DESIGN

Low step height and full swing gate provide easy access to platform and reduce chances of knee and neck strain.

#### **ROBUST RAIL SYSTEM**

Unique rail technology provides greater durability and resilience against wear on the job site.

#### **OVERSIZED 3.18 CM PINS**

Robust scissor stack requires no greasing and oversized pins reduce scissor sway.

#### **NON-MARKING WHEELS**

Protect sensitive floors and prevent surface scuffs on job site.

### NON-SKID DECK

Large durable platform provides ample working room.





HEIGHTS	METRIC	
Working Height	5.7 m	
Platform Height Max	3.7 m	
Platform Height Min	50.8 cm	
Ground Clearance Raised	1.3 cm	
Ground Clearance Lowered	7.3 cm	6
MEASUREMENTS		
Overall Length	157.5 cm	
Overall Width	76.2 cm	
Stowed Height	162.6 cm	
Platform Length	134.6 cm	Q
Platform Width	64.8 cm	
Platform Extension	76.2 cm	
PERFORMANCE		
Platform Capacity	249.5 kg	
Rated Occupancy	1 person	2
Extension Capacity	113.4 kg	$\otimes$
Weight	730.3 kg	24
Gradeability	25%	0
Inside Turn Radius	Zero	
Drive Speed Raised	0.3 m/s	
Drive Speed Lowered	1.0 m/s	
Lift Speed Up/Down	18/16 sec	
Power Source	(2) 12V DC	
Tires Front/Rear	20.3/30.5 cm	
FLOOR LOADING		
Min Wheel Load	707.8 kPa	
Max Wheel Load	949.6 kPa	~
Min Machine Load	6.6 kPa	
Max Machine Load	8.9 kPa	

#### 1-866-334-0756 // WWW.HYBRIDLIFTS.COM

This brochure is for illustrative purposes only and based on the latest information available at the time of printing. Hy-Brid Lifts reserves the right to make changes at any time, without notice, to specifications, standard and optional equipment. Hy-Brid Lifts™ is a trademark of Custom Equipment, Inc. ©2017 Custom Equipment, Inc. All rights reserved. 09/17 Part No. L01-17

